






All Rear Tires

10"-12" Snap-On

Half the weight, twice the wear, a softer ride and no flats. CEW's Urethane tires are state of the art in flatproof tire technology!

CHARCOAL GREY IS THE STANDARD COLOR FOR ALL TIRES UNLESS NOTED, CUSTOM COLORS AND SPECIFICATIONS ARE AVAILABLE

CROSS SECTION	TIRE SIZE INCHES	TIRE SIZE MILLIMETERS (ETRTO)	WHEEL SIZE	DESCRIPTION
	10 ¹ / ₂ " x 1 ¹ / ₂ "	270 x 38	12 ¹ / ₂ " x 2 ¹ / ₄ " (62-203)	Low profile Multi-rib tread
	11 ¹ / ₂ " x 1 ¹ / ₂ "	295 x 38	12 ¹ / ₂ " x 2 ¹ / ₄ " (62-203)	Medium profile Multi-rib tread
	10" x 2"	260 x 50	12 ¹ / ₂ " x 2 ¹ / ₄ " (62-203)	Ultra low profile Smooth tread
	12 ¹ / ₂ " x 2 ¹ / ₄ "	320 x 62 (62-203)	12 ¹ / ₂ " x 2 ¹ / ₄ " (62-203)	Full profile Knobby tread Reinforced beads
	12" x 2"	305 x 50	14" x 2 ¹ / ₄ " (57-254)	Ultra low profile Smooth tread

Note: Cross section drawings vary in scale









All Rear Tires

14"-19" Snap-On Drive

Half the weight, twice the wear, a softer ride and no flats. CEW's Urethane tires are state of the art in flatproof tire technology!

CHARCOAL GREY IS THE STANDARD COLOR FOR ALL TIRES UNLESS NOTED, CUSTOM COLORS AND SPECIFICATIONS ARE AVAILABLE

CROSS SECTION	TIRE SIZE INCHES	TIRE SIZE MILLIMETERS (ETRTO)	WHEEL SIZE	DESCRIPTION
	14 ¹ / ₂ " x 1 ¹ / ₂ "	350 x 38 (38-254)	14 ¹ / ₂ " x 2.125" (57-254)	Full profile Street tread Reinforced beads
	14" x 3"	360 x 85 (3.00-8)	3.00-8 (Quickie Alloy)	Full profile Knobby tread Reinforced beads
	14" x 3"	360 x 85 (3.00-8)	3.00-8 (Skyway Nylon)	Full profile Knobby tread Reinforced beads
	16" x 1.75"	405 x 47 (47-305)	16" x 1.75" (47-305)	Full profile Street tread Reinforced beads
	18" x 1.75"	455 x 47 (47-355)	18" x 1.75" (47-355)	Full profile Street tread Reinforced beads
	19" x 2.75"	488 x 70	20" x 2.125" (Skyway Nylon)	Medium profile All terrain tread Reinforced beads

Note: Cross section drawings vary in scale











All Rear Tires

20" Snap-On Drive

Half the weight, twice the wear, a softer ride and no flats. CEW's Urethane tires are state of the art in flatproof tire technology!

CHARCOAL GREY IS THE STANDARD COLOR FOR ALL TIRES UNLESS NOTED, CUSTOM COLORS AND SPECIFICATIONS ARE AVAILABLE

CROSS SECTION	TIRE SIZE INCHES	TIRE SIZE MILLIMETERS (ETRTO)	WHEEL SIZE	DESCRIPTION
	20" x 1"	490 x 25	20" x 1 ³ / ₈ " (37-451)	Pyramid style, low profile Cordless smooth tread
	20" x 1 ³ / ₈ "	508 x 37 (37-451)	20" x 1 ³ / ₈ " (37-451)	Full profile Street tread Reinforced beads
	20" x 1 ¹ / ₂ "	500 x 38	20" x 1.75" (47-406)	Full profile All terrain tread Reinforced beads
	20" x 1.75"	500 x 47 (47-406)	20" x 1.75" (47-406)	Full profile Street tread Reinforced beads
	20" x 2.125"	500 x 47 (57-406)	20" x 2.125" (E&J Alloy)	Full profile Lug tread Reinforced beads
	20" x 2.125"	500 x 47 (57-406)	20" x 2.125" (Invacare Alloy) (Skyway Nylon)	Full profile Lug tread Reinforced beads
	20" x 2.125"	500 x 47 (57-406)	20" x 2.125" (Quickie Alloy)	Full profile Lug tread Reinforced beads
	19" x 2.75"	488 x 70	20" x 2.125" (Skyway Nylon)	Medium profile All terrain tread Reinforced beads

Note: Cross section drawings vary in scale










All Rear Tires

22" Snap-On Drive

Half the weight, twice the wear, a softer ride and no flats. CEW's Urethane tires are state of the art in flatproof tire technology!

CHARCOAL GREY IS THE STANDARD COLOR FOR ALL TIRES UNLESS NOTED, CUSTOM COLORS AND SPECIFICATIONS ARE AVAILABLE

CROSS SECTION	TIRE SIZE INCHES	TIRE SIZE MILLIMETERS (ETRTO)	WHEEL SIZE	DESCRIPTION
	22" x 1"	540 x 25	22" x 1 ³ / ₈ " (489 & 501 mm)	Pyramid / Cordless Low profile, smooth tread
	22" x 1"	540 x 25	22" x 1 ³ / ₈ " (489 mm)	Pyramid, low profile Smooth tread Reinforced beads
	22" x 1"	540 x 25	22" x 1 ³ / ₈ " (501 mm)	Pyramid, low profile Smooth tread Reinforced beads
	22" x 1"	560 x 25	22" x 1" (for solid tires)	Pyramid profile Smooth tread Reinforced beads
	22" x 1 ¹ / ₄ "	560 x 28 (28-501)	22" x 1 ³ / ₈ " (501 mm)	Full profile Chevron tread Reinforced beads
	22" x 1 ¹ / ₄ "	560 x 28 (28-501)	22" x 1 ³ / ₈ " (501 mm)	Full profile Street tread Reinforced beads
	22" x 1 ³ / ₈ "	560 x 28 (37-501)	22" x 1 ³ / ₈ " (501 mm)	Full profile Touring tread Reinforced beads

Note: Cross section drawings vary in scale











All Rear Tires

24" Snap-On Drive

Half the weight, twice the wear, a softer ride and no flats. CEW's Urethane tires are state of the art in flatproof tire technology!

CHARCOAL GREY IS THE STANDARD COLOR FOR ALL TIRES UNLESS NOTED, CUSTOM COLORS AND SPECIFICATIONS ARE AVAILABLE

CROSS SECTION	TIRE SIZE INCHES	TIRE SIZE MILLIMETERS (ETRTO)	WHEEL SIZE	DESCRIPTION
	24" x 7/8"	590 x 22	24" x 7/8" (Sun Metal Narrow)	Pyramid style, low profile Cordless smooth tread
	24" x 1"	590/615 x25 (Dependent on wheel)	24" x 1 3/8" 24" x 1"	Pyramid style, low profile Cordless smooth tread
	24" x 1"	590x 25	24" x 1 3/8" (540 mm)	Pyramid style, low profile Smooth tread Reinforced beads
	24" x 1"	615 x 25	24" x 1" (Invacare)	Pyramid style Smooth tread Reinforced beads
	24" x 1"	615 x 25	24" x 1" (E & J)	Pyramid style Smooth tread Reinforced beads
	24" x 1"	615 x 25 (25-540)	24" x 1 3/8" (540 mm)	Full profile Turbo tread Reinforced beads
	24" x 1 1/4"	615 x 32 (32-540)	24" x 1 3/8" (540 mm)	Full profile Street tread
	24" x 1 3/8"	615 x 32 (37-540)	24" x 1 3/8" (540 mm)	Full profile Touring tread Reinforced beads

Note: Cross section drawings vary in scale







All Rear Tires

25"-26" Snap-On Drive

Half the weight, twice the wear, a softer ride and no flats. CEW's Urethane tires are state of the art in flatproof tire technology!

CHARCOAL GREY IS THE STANDARD COLOR FOR ALL TIRES UNLESS NOTED, CUSTOM COLORS AND SPECIFICATIONS ARE AVAILABLE

CROSS SECTION	TIRE SIZE INCHES	TIRE SIZE MILLIMETERS (ETRTO)	WHEEL SIZE	DESCRIPTION
	25" x 1"	640 x 25 (25-559)	559 mm	Full profile Turbo tread Reinforced beads
	25" x 1 ³ / ₈ "	640x 37 (37-559)	559 mm	Full profile Touring tread Reinforced beads
	26" x 1"	665 x 25 (25-590)	590 mm	Full profile Turbo tread Reinforced beads
	26" x 1 ³ / ₈ "	665 x 37 (37-590)	590 mm	Full profile Touring tread Reinforced beads

Note: Cross section drawings vary in scale

The tires on this page fit 559mm (25 x 1 or 26 x 1) wheels and 590mm (26 x 1³/₈) wheels. They are made in 24" molds and fitted with special color coded cords

to fit the larger diameter wheels. Tires with red cords are designed to fit 559mm wheels. Tires with gold cords are designed to fit 590mm wheels.

